

2/19/28

DIALOG(R) File 347:JAPIO

(c) 2003 JPO & JAPIO. All rts. reserv.

05298713 **Image available**

SEALING DEVICE FOR BEARING FOR WATER PUMP

PUB. NO.: 08-254213 [JP 8254213 A]
PUBLISHED: October 01, 1996 (19961001)
INVENTOR(s): HATABU SHIYOUJI
APPLICANT(s): KOYO SEIKO CO LTD [000124] (A Japanese Company or
 Corporation), JP (Japan)
APPL. NO.: 07-086260 [JP 9586260]
FILED: March 17, 1995 (19950317)
INTL CLASS: [6] F16C-033/78; F16J-015/32 ; F16J-015/40
JAPIO CLASS: 22.1 (MACHINERY -- Machine Elements); 24.1 (CHEMICAL
 ENGINEERING -- Fluid Transportation)

ABSTRACT

PURPOSE: To prevent moisture from entering a bearing with a simple structure and a small cost.

CONSTITUTION: A rolling body is arranged in a annular space between an outer ring 4 fixed to a static member and a rotary **shaft** 1 which is provided with an impeller on one side, a driving pulley on the other side, and rotated in one direction. A **seal** member 7 is fixed to an end of the outer ring 4 and in a sliding contact with the rotary **shaft** 1 for sealing the circular space. In such a sealing device of a **bearing** for a water pump, branched **seal** lips 7a, 7b are formed on a sliding contact end of the **seal** member 7 which is in sliding contact with the rotary **shaft** 1. A pumping function generating groove 8 or a rib is formed on the surface of the rotary **shaft** 1 at its position which is in sliding contact with the outer **seal** tip 7a, or the rear surface of the **seal** lip, in the direction for discharging moisture outward of the **bearing** during rotation of the rotary **shaft** 1.

C:\Program Files\Dialog\DialogLink\Graphics\20.bmp

